



Ref.: BM-M2204-28 KV:1480

Zellen Cells	KV	Leerlauf- strom bei 10V Le courant	Max. Leistung Puissance	Widerstand Résistance	Durchmesser Diamètre	Länge Longeur	Stator Ø	Stator Länge Longeur	Welle Ø Axe Ø
2-3	1480	0.45A	110W	290mΩ	27mm	20.5mm	22mm	4mm	3mm
Modellgewicht Poid de modell		Empfohlener Propeller Recommande Hélice		Regler Controlleur		Gewicht Poids			
120-200g		2S 8x4"		2S 9x4.7"		10A		22g	



2204 KV:1480 (Testet with 20A ESC)				
Propeller Hélice	Spannung V Tension V	Strom A Courant A	Leistung W Puissance W	Schub g
8 x 4"	6.4	3.4	21	190
	7	3.9	27	240
	7.4	4.3	31	280
9 x 4,7"	6.4	5.7	36	310
	7	6.3	44	340
	7.4	6.9	51	390

Zubehör: Accessoires:

Ref.: BM-M2204-SH
 Motorwelle zu 2204 Serie
 Axe de moteur pour série 2204

Ref.: BM-MSP22
 Montagekreuz, Spannkonus und Spinner
 Support moteur, cône de serrage et nez d'hélice